

# MAX 7005 MULTIPURPOSE CLEANER

Concentrated NON-ACIDIC Multipurpose cleaner to remove Epoxy & Cementitious Grout residues and inorganic dirt.

## **DESCRIPTION:**

**MAX 7005 MULTIPURPOSE CLEANER** is a concentrated NON ACIDIC Multipurpose cleaner specifically developed to wash and clean after installation of Tile / Stone.

The action of **MAX 7005 MULTIPURPOSE CLEANER** eliminates all residues of Epoxy, Cementitious grout, paint drop, Adhesives, RMC & Scaffolding, Texture Paint without changing the colour of joints and restoring the original appearance to treated surfaces. It is also extremely effective when it comes to removing inorganic dirt.

## **FEATURES & BENEFITES:**

- Ready to use
- A versatile product, suitable for use on different types of Surfaces
- High cleaning action
- Effective on Epoxy / Cement-based residues
- Easy application

## USES:

This product can be used on both indoor and outdoor surfaces.

Suitable for use on: Marble-quartz agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Tuff


APPLICATION EQUIPMENT: Cloth, Mop etc.

## **APPLICATION STEPS :**

## Preparing and cleaning the surface

Cleaning after the installation process must be completed at least 48 hours after grouting the surfaces.

 Before proceeding to wash the surface, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner.



- Any adjacent surfaces not being treated with the product must be protected.
- Apply the product to surfaces with a temperature of between +5°C and +48
- Begin to work the product over the surface, rubbing the surface with the tool of choice.
- Leave the product to act for 10 15 minutes, continuing to wipe over the surface with your tool of choice to boost and aid the cleansing action of the product.
- After working the product, remove all residues and rinse the whole floor with plenty of water.
- If the result is only partially achieved, repeat the application process following the same steps and if necessary, slightly increase the concentration of the product in water.

## INSTRUCTIONS AND GUIDELINES:

- Wait at least 48 hours after grouting
- Never apply the product to a wet surface
- Never use in conjunction with other chemical products.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

# **TECHNICAL INFORMATION:**

Appearance	: Clear Pale Yellow Liquid
Odour	: Sweet Smell
рН	:7 <u>±</u> 1

# APPLICATION:

Before applying the product to the whole surface, always test a small, unexposed area or unused piece to check its suitability for use.



Regd. Office: 2<sup>nd</sup> Floor, Neelmani Chambers, B/h. Sales India, Ashram Road, Ahmedabad - 380009. Gujarat, INDIA Ph.: +91 - 79 - 26584951 | 26584197 | 26573759 E-mail: info@semitrone.com | www.semitrone.com



#### PACKING:

500 ml, 1 Ltr, 5 Ltr, 10 Ltr and 20 Ltr

## **HEATLH & SAFTEY:**

- Use rubber hand gloves & safety goggles, while using MAX 7005 MULTIPURPOSE CLEANER In case of contact with skin, wash with plenty of water.
- Keep out of reach of children

### **STORAGE & LIFE:**

Best before two years from the date manufacture when in sealed pack and stored in cool & dry place in unopened condition away from direct sunlight.

### **TECHNICAL INFORMATION & SERVICES:**

Further information and advice, including practical demonstration are freely available with the Technical Service Department of **SEMITRONE CONCHEM PVT LTD - AHMEDABAD**.

**DISCLAIMER**: The product information & application details given by the company & its agents has been provided in good faith& meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results.



Regd. Office: 2<sup>nd</sup> Floor, Neelmani Chambers, B/h. Sales India, Ashram Road, Ahmedabad - 380009. Gujarat, INDIA Ph.: +91 - 79 - 26584951 | 26584197 | 26573759 E-mail: info@semitrone.com | www.semitrone.com

