

## **MAX 9002 STONE JOINT FILLER**

(Above 5 mm groove)

(Sanded Grout)

### DESCRIPTION:

**MAX 9002 STONE JOINT FILLER** is a blend of specially selected cements, poly propylene fibers, fillers, high grade pigments and synthetic organic polymers. It is polymer modified highly water resist, peel proof and crack proof tile joint filler available in more than 38 attractive colours. Suitable for more than 5 mm width. It complies to **BS 5385**

### AREA OF APPLICATION:

- Ideal for all kind of joints in Exterior Walls & Exterior Floors
- Pavers Flooring, Parking area, etc.
- Ideal for Vitrified, Kota, Marble & Granite

### ADVANTAGES:

- Can be used for filling joints of various kinds of tiles and stones
- Easy to use and consistent in quality
- Highly water resist & peel proof
- Highly stain resistance/ Acid proof
- High damp resistance
- Available in attractive colour range

### HOW TO USE:

- Tile joint must be clean, free from any dust or other contaminates.
- Fill the joints after minimum 24 hours from tile fixed with chemical.
- Mix Stone filler and water in 3 : 1 ratio
- Wait for ten minutes for proper chemical action.
- Fill the joint properly.
- Clean the extra joint filler from tile surface with wet cotton cloth after 1.5 hours.
- Clean the joints with dry cotton cloth after 24 hours.

### TECHNICAL INFORMATION:

- Density : Wet : 1.85 kg/ltr
- Dry : 1.78 kg/ltr
- Compressive Strength : 34.45 N/mm<sup>2</sup>  
@ 28 days
- Flexural Strength : 3.65 N/mm<sup>2</sup>  
@ 28 days
- Working Time : 30 minutes

- Curing : minimum 48 hours
- Mixing Ratio : Approx. 0.32 to 0.34 % by weight of joint filler i. e. 1.6 to 1.7 liter water per 5 kg joint filler.

### Packing:

10 Kg

### HEALTH & SAFETY:

- Use rubber hand gloves & safety goggles, while using **MAX 9002 STONE JOINT FILLER**
- In case of contact with skin, wash with plenty of water.
- Keep out of reach of children

### STORAGE & LIFE:

Best before one and half years from the date manufacture when in sealed pack and stored in cool & dry place in unopened condition away from direct sunlight.

### TECHNICAL INFORMATION & SERVICES:

Further information and advice, including practical demonstration are freely available with the Technical Service Department of **SEMITRONE CONCHEM PVT LTD - AHMEDABAD.**

**DISCLAIMER:** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results.



Regd. Office: 2<sup>nd</sup> Floor, Neelmani Chambers, B/h. Sales India,  
 Ashram Road, Ahmedabad - 380009. Gujarat, INDIA  
 Ph.: +91 - 79 - 26584951 | 26584197 | 26573759  
 E-mail: info@semitrone.com | www.semitrone.com

**SEMITRONE**  
**CONCHEM PVT. LTD.**  
 A CONSTRUCTIONS CHEMICAL COMPANY