# **TECHNICAL DATASHEET**



## **MAX 2010 RUST-O-CON**

(Water Based Rust Convertor (Remove, Convert and Protect))

#### **DESCRIPTION:**

MAX 2010 RUST-O-CON is greenish acidic clear ready to use rust converter. Its convert the rust in protective coating. Meets the requirements of IS 13515:1992, BS EN 12508:2000

## **Area of Application:**

On re-bars during repairs to reinforced concrete structures. Maintenance of mild steel structures like tanks, water pipelines, shuttering plates and other corroded steel

### Advantage:

Converts rust in protective coating, Does not negatively affect rebar's adhesion to concrete, Can be applied under varying weather conditions

#### Coverage:

Approximately 110 to 130 sq<sup>2</sup> per Ltr depend upon Rusted Surface.

#### PACKING:

1 Ltr, 5 ltr, 20 ltr, 200 ml & 500 ml

## **STORAGE & LIFE:**

Best before one and half years from the date manufacture when in sealed pack and stored in cool & dry place in unopened condition away from direct sunlight.

## **HEATLH & SAFTEY:**

- Use rubber hand gloves & safety goggles, while using MAX 2010 RUST-O-CON
- In case of contact with skin, wash with plenty of water.
- Keep out of reach of children

#### **TECHNICAL INFORMATION & SERVICES:**

Further information and advice, including practical demonstration are freely available with the Technical Service Department of **SEMITRONE CONCHEM PVT LTD - AHMEDABAD**.

**DISCLAIMER**: The product information & application details given by the company & its agents has been provided in good faith& meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results.



