

## **MAX 1005 PAVESEAL (S/B)**

**(Bonding Agent for Plaster)**

### **DESCRIPTION:**

**MAX 1005 PAVE SEAL (S/B)** is a transparent acrylic UV TPR that provides resistance to weathering, foot traffic and offers UV and weathering properties. Typical applications include a clear acrylic UV TPR for Paver Block, Chequered Tile.

### **ADVANTAGES:**

- Color enhancement of pavers & tiles
- Excellent adhesion to paver block/tile
- Good abrasion resistance
- Resistance to weathering and UV
- Provides glossy finish
- Clear transparent coating
- Resistance to foot traffic
- Offers waterproofing properties
- Easy to apply

### **AREA OF APPLICATION :**

For Sealing the Paver Block, Chequered Tile

### **SURFACE PREPARATION:**

Ensure that the surface to be sealed is free from rust, grease, oil & loose material before application

### **METHOD OF APPLICATION:**

After proper surface preparation or cleaning, apply first coat of **MAX 1005 Pave Seal (S/B)** UV TPR coating by brush or roller Allow drying for 24 hrs to hard dry.

### **TECHNICAL SPECIFICATION:**

Chemical Base : Specially engineered  
polymer acrylic

Appearance : Clear transparent Liquid

Density : 1.25

Viscosity : 130

### **COVERAGE:**

45 Sq.Ft/ ltr. Coat.\*

\*Depend upon porosity of surface.

### **PACKING:**

25 kg

### **STORAGE & LIFE:**

Best before two years from the date manufacture when in sealed pack and stored in cool & dry place in unopened condition away from direct sunlight.

### **HEALTH & SAFETY:**

- Use rubber hand gloves & safety goggles, while using **MAX 1005 PAVE SEAL (S/B)**
- In case of contact with skin, wash with plenty of water.
- Keep out of reach of children

### **TECHNICAL INFORMATION & SERVICES:**

Further information and advice, including practical demonstration are freely available with the Technical Service Department of **SEMITRONE CONCHEM PVT LTD - AHMEDABAD.**

**DISCLAIMER:** The product information & application details given by the company & its agents has been provided in good faith & meant to serve only as a general guideline during usage. Users are advised to carry out tests & take trials to ensure on the suitability of products meeting their requirement prior to full scale usage of our products. Since the correct identification of the problems, quality of other materials used and the on-site workmanship are factors beyond our control, there are no expressed or implied guarantee / warranty as to the results obtained. The company does not assume any liability or consequential damage for unsatisfactory results.

